

PRODUCT-DETAILS

3GAA222210-HSL

M3AA 225SMA 4



General Information

Product ID	3GAA222210-HSL
ABB Type Designation	M3AA 225SMA 4
Catalog Description	M3AA 225SMA 4

Additional Information

ABB Type Designation	M3AA 225SMA 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6313-2Z/C3
Bearing NDE	6210-2Z/C3
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	37.00 kW	1480 r/min	69.30 A	0.820	93.90 %	238.73 N·m	7.50
D	--	50 Hz	230 V	37.00 kW	1480 r/min	120.00 A	0.820	93.90 %	238.73 N·m	7.50
Y	--	50 Hz	415 V	37.00 kW	1482 r/min	68.50 A	0.800	93.90 %	238.41 N·m	7.90
Y	--	60 Hz	440 V	37.00 kW	1781 r/min	61.90 A	0.830	94.50 %	198.39 N·m	7.90
Y	--	60 Hz	460 V	37.00 kW	1783 r/min	59.90 A	0.820	94.50 %	198.16 N·m	8.60

Gross Weight	259 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 93.9 % Partial Load (75%) 94.7 % Partial Load (50%) 94.5 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 94.5 % Partial Load (75%) 94.9 % Partial Load (50%) 94.4 %
IM Class	IMB35 IM2001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 225SMA 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Pre Modified Motor Product ID	3GAA222210-ASL
Product Name	3-Phase squirrel cage motor
Product Net Weight	249 kg
Product Type	5AA3__M3AA_IE3_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA222051-HSL
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

