

PRODUCT-DETAILS

3GAA222230-HEK

M3AA 225SMC 4



General Information

Product ID	3GAA222230-HEK
ABB Type Designation	M3AA 225SMC 4
Catalog Description	M3AA 225SMC 4

Additional Information

ABB Type Designation	M3AA 225SMC 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6313-2Z/C3
Bearing NDE	6212-2Z/C3
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015290
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	50 Hz	500 V	53.00 kW	1482 r/min	77.60 A	0.830	94.50 %	341.34 N·m	8.70

Gross Weight	328 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 94.5 %

	Partial Load (75%) 94.7 %
	Partial Load (50%) 94.2 %
IE Class Data (60 Hz)	IE Class IE3
	Full Load (100%) 95.0 %
	Partial Load (75%) 94.8 %
	Partial Load (50%) 93.8 %
IM Class	IMB35 IM2001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 225SMC 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Pre Modified Motor	3GAA222230-AEK
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	318 kg
Product Type	3AA3_M3AA_IE3_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA222053-HEK
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	E
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors



