

PRODUCT-DETAILS

3GAA223210-ADF

M2AA 225SMA 6



General Information

Product ID	3GAA223210-ADF
ABB Type Designation	M2AA 225SMA 6
Catalog Description	M2AA 225SMA 6

Additional Information

ABB Type Designation	M2AA 225SMA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6213-2Z/C3
Bearing NDE	6210-2Z/C3
Country of Origin	Spain (ES) Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	30.00 kW	986 r/min	33.30 A	0.830	92.20 %	290.00 N·m	6.90
D	--	50 Hz	400 V	30.00 kW	986 r/min	57.20 A	0.830	92.20 %	290.00 N·m	6.90
D	--	50 Hz	415 V	30.00 kW	986 r/min	56.30 A	0.800	92.20 %	290.00 N·m	7.20
D	--	60 Hz	460 V	30.00 kW	1188 r/min	50.10 A	0.830	93.00 %	241.00 N·m	7.90

Gross Weight	275 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class NA Full Load (100%) 92.2 % Partial Load (75%) 93.1 % Partial Load (50%) 93.1 %
IE Class Data (60 Hz)	IE Class NA Full Load (100%) 93.0 % Partial Load (75%) 93.5 % Partial Load (50%) 92.8 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2AA 225SMA 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	265 kg
Product Type	2AA2__M2AA__IE2_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA223061-ADA
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Aluminum Motors

