

PRODUCT-DETAILS

3GBA072320-ADC

M2BAX 71MB 4



General Information

Product ID	3GBA072320-ADC
ABB Type Designation	M2BAX 71MB 4
Catalog Description	M2BAX 71MB 4

Additional Information

ABB Type Designation	M2BAX 71MB 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6203-2Z/C3
Bearing NDE	6202-2Z/C3
Country of Origin	China (CN) Poland (PL)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	0.37 kW	1416 r/min	0.59 A	0.720	72.70 %	2.49 N·m	4.90
D	--	50 Hz	400 V	0.37 kW	1416 r/min	1.03 A	0.720	72.70 %	2.49 N·m	4.90
Y	--	50 Hz	660 V	0.37 kW	1405 r/min	0.59 A	0.760	72.70 %	2.51 N·m	4.70
D	--	50 Hz	380 V	0.37 kW	1405 r/min	1.02 A	0.760	72.70 %	2.51 N·m	4.70
D	--	60 Hz	440 V	0.37 kW	1722 r/min	0.95 A	0.700	72.00 %	2.05 N·m	5.70
D	--	60 Hz	460 V	0.37 kW	1729 r/min	0.96 A	0.670	72.00 %	2.04 N·m	5.80

Gross Weight	13 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 72.7 % Partial Load (75%) 71.6 % Partial Load (50%) 66.6 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 72.0 % Partial Load (75%) 69.6 % Partial Load (50%) 63.1 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2BAX 71MB 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	10 kg
Product Type	EBA2__M2BAX_CI
Quote Only	No
SCIP	d19446d4-4db6-4ddb-826d-2341a0f7dd46 Finland (FI)
Selling Unit of Measure	piece
Stocked At (Warehouses)	Shanghai, China
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Cast Iron Motors

