

PRODUCT-DETAILS

3GBA072320-ADCCN

M2BAX 71MB4



General Information

Product ID	3GBA072320-ADCCN
ABB Type Designation	M2BAX 71MB 4
Catalog Description	M2BAX 71MB4

Additional Information

ABB Type Designation	M2BAX 71MB 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6203-2Z/C3
Bearing NDE	6202-2Z/C3
Country of Origin	China (CN)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	0.37 kW	1418 r/min	0.62 A	0.690	72.70 %	2.50 N·m	5.00
D	--	50 Hz	400 V	0.37 kW	1418 r/min	1.08 A	0.690	72.70 %	2.50 N·m	5.00
Y	--	50 Hz	660 V	0.37 kW	1407 r/min	0.61 A	0.740	72.70 %	2.52 N·m	4.80
D	--	50 Hz	380 V	0.37 kW	1407 r/min	1.07 A	0.740	72.70 %	2.52 N·m	4.80
D	--	60 Hz	440 V	0.37 kW	1723 r/min	0.97 A	0.680	72.00 %	2.06 N·m	5.70
D	--	60 Hz	460 V	0.37 kW	1731 r/min	0.99 A	0.640	72.00 %	2.05 N·m	5.90

Gross Weight	13 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 72.7 % Partial Load (75%) 70.4 % Partial Load (50%) 65.0 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 72.0 % Partial Load (75%) 68.1 % Partial Load (50%) 61.2 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2BAX 71MB4
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	10 kg
Product Type	CBA2__M2BAX_CI
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Shanghai, China Guangzhou, China
Temperature Class Default	--
Temperature Rise	80 K
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Cast Iron Motors

