

PRODUCT-DETAILS

3GBA072320-CDC

No Description Available



General Information

Product ID	3GBA072320-CDC
ABB Type Designation	M2BAX 71MB 4
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M2BAX 71MB 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6203-2Z/C3
Bearing NDE	6202-2Z/C3
Country of Origin	Poland (PL)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	0.37 kW	1416 r/min	0.59 A	0.720	72.70 %	2.49 N·m	4.90
D	--	50 Hz	400 V	0.37 kW	1416 r/min	1.03 A	0.720	72.70 %	2.49 N·m	4.90
Y	--	50 Hz	660 V	0.37 kW	1405 r/min	0.59 A	0.760	72.70 %	2.51 N·m	4.70
D	--	50 Hz	380 V	0.37 kW	1405 r/min	1.02 A	0.760	72.70 %	2.51 N·m	4.70
D	--	60 Hz	440 V	0.37 kW	1722 r/min	0.95 A	0.700	72.00 %	2.05 N·m	5.70
D	--	60 Hz	460 V	0.37 kW	1729 r/min	0.96 A	0.670	72.00 %	2.04 N·m	5.80

Gross Weight	13 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 72.7 % Partial Load (75%) 71.6 % Partial Load (50%) 66.6 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 72.0 % Partial Load (75%) 69.6 % Partial Load (50%) 63.1 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	10 kg
Product Type	EBA2__M2BAX_CI
Quote Only	No
SCIP	d19446d4-4db6-4ddb-826d-2341a0f7dd46 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Cast Iron Motors

