

PRODUCT-DETAILS

3GBA073410-BSD

M2BAX 71MLA 6



General Information

Product ID	3GBA073410-BSD
ABB Type Designation	M2BAX 71MLA 6
Catalog Description	M2BAX 71MLA 6

Additional Information

ABB Type Designation	M2BAX 71MLA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6203-2Z/C3
Bearing NDE	6202-2Z/C3
Country of Origin	China (CN)
Customs Tariff Number	85015100
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	0.25 kW	926 r/min	0.80 A	0.670	68.60 %	2.58 N·m	4.30
D	--	50 Hz	230 V	0.25 kW	926 r/min	1.40 A	0.670	68.60 %	2.58 N·m	4.30
Y	--	50 Hz	380 V	0.25 kW	915 r/min	0.80 A	0.710	68.60 %	2.58 N·m	3.80
D	--	50 Hz	220 V	0.25 kW	915 r/min	1.39 A	0.710	68.60 %	2.58 N·m	4.10

Gross Weight	16 kg
IC Class	IC411

IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 68.6 % Partial Load (75%) 66.2 % Partial Load (50%) 60.9 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 59.5 % Partial Load (75%) 53.7 % Partial Load (50%) 44.6 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2BAX 71MLA 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	13 kg
Product Type	EBA3__M2BAX_CI
Quote Only	No
SCIP	d19446d4-4db6-4ddb-826d-2341a0f7dd46 Finland (FI)
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany Shanghai, China
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE3 Premium Efficiency Cast Iron Motors



