

PRODUCT-DETAILS

3GBA081310-CDC

No Description Available



General Information

Product ID	3GBA081310-CDC
ABB Type Designation	M2BAX 80MA 2
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M2BAX 80MA 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6204-2Z/C3
Bearing NDE	6203-2Z/C3
Country of Origin	Poland (PL)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	0.75 kW	2843 r/min	0.99 A	0.810	77.40 %	2.51 N·m	6.20
D	--	50 Hz	400 V	0.75 kW	2843 r/min	1.71 A	0.810	77.40 %	2.51 N·m	6.20
Y	--	50 Hz	660 V	0.75 kW	2819 r/min	1.00 A	0.850	77.40 %	2.51 N·m	5.80
D	--	50 Hz	380 V	0.75 kW	2819 r/min	1.73 A	0.850	77.40 %	2.56 N·m	5.80
D	--	60 Hz	440 V	0.75 kW	3453 r/min	1.52 A	0.820	75.50 %	2.09 N·m	7.10
D	--	60 Hz	460 V	0.75 kW	3469 r/min	1.52 A	0.780	75.50 %	2.08 N·m	7.40

Gross Weight	17 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 77.4 % Partial Load (75%) 76.3 % Partial Load (50%) 73.7 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 75.5 % Partial Load (75%) 72.7 % Partial Load (50%) 67.8 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	14 kg
Product Type	EBA2__M2BAX_CI
Quote Only	No
SCIP	d19446d4-4db6-4ddb-826d-2341a0f7dd46 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Cast Iron Motors

