

PRODUCT-DETAILS

3GBA081320-BST

No Description Available



General Information

Product ID	3GBA081320-BST
ABB Type Designation	M2BAX 80MB 2
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M2BAX 80MB 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6204-2Z/C3
Bearing NDE	6203-2Z/C3
Country of Origin	China (CN)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	1.10 kW	2845 r/min	2.44 A	0.830	75.00 %	3.67 N·m	6.20
D	--	50 Hz	230 V	1.10 kW	2845 r/min	4.23 A	0.830	75.00 %	3.67 N·m	6.20
Y	--	50 Hz	380 V	1.10 kW	2819 r/min	2.50 A	0.860	75.00 %	3.67 N·m	5.60
D	--	50 Hz	220 V	1.10 kW	2819 r/min	4.33 A	0.860	75.00 %	3.67 N·m	5.60
Y	--	60 Hz	440 V	1.10 kW	3445 r/min	2.18 A	0.830	78.50 %	3.00 N·m	6.90
Y	--	60 Hz	460 V	1.10 kW	3460 r/min	2.16 A	0.800	78.50 %	2.99 N·m	7.30

Gross Weight	18 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class NA Full Load (100%) 75.0 % Partial Load (75%) 74.6 % Partial Load (50%) 72.5 %
IE Class Data (60 Hz)	IE Class NA Full Load (100%) 78.5 % Partial Load (75%) 77.0 % Partial Load (50%) 73.5 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	15 kg
Product Type	EBA1__M2BAX_CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE1 Standard Efficiency Cast Iron Motors

