

PRODUCT-DETAILS

3GBA083310-BSC

M2BAX 80MA 6



General Information

Product ID	3GBA083310-BSC
ABB Type Designation	M2BAX 80MA 6
Catalog Description	M2BAX 80MA 6

Additional Information

ABB Type Designation	M2BAX 80MA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6204-2Z/C3
Bearing NDE	6203-2Z/C3
Country of Origin	China (CN) Poland (PL)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	0.37 kW	936 r/min	1.08 A	0.730	67.60 %	3.82 N·m	4.40
D	--	50 Hz	230 V	0.37 kW	936 r/min	1.87 A	0.730	67.60 %	3.82 N·m	4.40
Y	--	50 Hz	380 V	0.37 kW	936 r/min	1.08 A	0.770	67.60 %	3.88 N·m	4.20
D	--	50 Hz	220 V	0.37 kW	936 r/min	1.87 A	0.770	67.60 %	3.88 N·m	4.20
Y	--	60 Hz	440 V	0.37 kW	1139 r/min	1.05 A	0.720	64.00 %	3.10 N·m	4.90
Y	--	60 Hz	460 V	0.37 kW	1145 r/min	1.07 A	0.680	64.00 %	3.11 N·m	5.00
Gross Weight										17 kg
IC Class										IC411
IE Class Data (50 Hz)										IE Class IE2 Full Load (100%) 67.6 % Partial Load (75%) 67.2 % Partial Load (50%) 62.9 %
IE Class Data (60 Hz)										IE Class IE2 Full Load (100%) 64.0 % Partial Load (75%) 61.8 % Partial Load (50%) 55.2 %
IM Class										IMB5 IM3001
IP Class										IP55
Insulation Class										ICLF
Invoice Description										M2BAX 80MA 6
Lubrication										For life
Made To Order										No
Minimum Order Quantity										1 piece
Number of Poles (High)										6
Order Multiple										1 piece
Package Level 1 Units										0 carton
Product Name										3-Phase squirrel cage motor
Product Net Weight										14 kg
Product Type										EBA2__M2BAX_CI
Quote Only										No
SCIP										d19446d4-4db6-4ddb-826d-2341a0f7dd46 Finland (FI)
Selling Unit of Measure										piece
Standards										IEC 60034-1
Starting of Motor										Direct Online
Stocked At (Warehouses)										Shanghai, China
Temperature Class Default										--
Temperature Rise										80 K
Terminator Box Location										D-End top
Two Speed Motor										No
Type of Duty										S1
UNSPSC										26101100
Voltage Code										S
WEEE Category										5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Cast Iron Motors

