

PRODUCT-DETAILS

3GBA091510-ADCCN

M2BAX 90LA2



General Information

Product ID	3GBA091510-ADCCN
ABB Type Designation	M2BAX 90LA 2
Catalog Description	M2BAX 90LA2

Additional Information

ABB Type Designation	M2BAX 90LA 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	China (CN)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	2.20 kW	2894 r/min	2.59 A	0.840	83.20 %	7.25 N·m	7.70
D	--	50 Hz	400 V	2.20 kW	2894 r/min	4.48 A	0.840	83.20 %	7.25 N·m	7.70
Y	--	50 Hz	660 V	2.20 kW	2882 r/min	2.64 A	0.870	83.20 %	7.25 N·m	7.10
D	--	50 Hz	380 V	2.20 kW	2882 r/min	4.58 A	0.870	83.20 %	7.25 N·m	7.10
D	--	60 Hz	440 V	2.20 kW	3496 r/min	3.85 A	0.890	85.50 %	6.00 N·m	8.90
D	--	60 Hz	460 V	2.20 kW	3505 r/min	3.93 A	0.830	85.50 %	5.99 N·m	9.20

Gross Weight	27 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 83.2 % Partial Load (75%) 83.0 % Partial Load (50%) 81.4 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 85.5 % Partial Load (75%) 84.4 % Partial Load (50%) 82.0 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2BAX 90LA2
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	24 kg
Product Type	CBA2__M2BAX_CI
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Shanghai, China Guangzhou, China
Temperature Class Default	--
Temperature Rise	80 K
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Cast Iron Motors

