

PRODUCT-DETAILS

3GBA091510-ASC

M2BAX 90LA 2



General Information

Product ID	3GBA091510-ASC
ABB Type Designation	M2BAX 90LA 2
Catalog Description	M2BAX 90LA 2

Additional Information

ABB Type Designation	M2BAX 90LA 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Poland (PL) China (CN)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	2.20 kW	2896 r/min	4.48 A	0.840	83.20 %	7.25 N·m	7.70
D	--	50 Hz	230 V	2.20 kW	2896 r/min	7.76 A	0.840	83.20 %	7.25 N·m	7.70
Y	--	50 Hz	380 V	2.20 kW	2881 r/min	4.58 A	0.870	83.20 %	7.25 N·m	7.10
D	--	50 Hz	220 V	2.20 kW	2881 r/min	7.93 A	0.870	83.20 %	7.25 N·m	7.10
Y	--	60 Hz	460 V	2.20 kW	3505 r/min	3.93 A	0.830	81.50 %	5.99 N·m	9.20
Y	--	60 Hz	440 V	2.20 kW	3496 r/min	3.85 A	0.890	81.50 %	6.00 N·m	8.90

Gross Weight	27 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 83.2 % Partial Load (75%) 82.9 % Partial Load (50%) 81.2 %
IE Class Data (60 Hz)	IE Class IE1 Full Load (100%) 81.5 % Partial Load (75%) 80.0 % Partial Load (50%) 77.0 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2BAX 90LA 2
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	24 kg
Product Type	EBA2__M2BAX_CI
Quote Only	No
SCIP	d19446d4-4db6-4ddb-826d-2341a0f7dd46 Finland (FI)
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Menden, Germany Shanghai, China
Temperature Class Default	--
Temperature Rise	80 K
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Cast Iron Motors

