

PRODUCT-DETAILS

3GBA101510-BSC

M2BAX 100LA 2



General Information

Product ID	3GBA101510-BSC
ABB Type Designation	M2BAX 100LA 2
Catalog Description	M2BAX 100LA 2

Additional Information

ABB Type Designation	M2BAX 100LA 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	China (CN) Poland (PL)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	3.00 kW	2919 r/min	6.08 A	0.850	84.60 %	9.81 N·m	8.70
D	--	50 Hz	230 V	3.00 kW	2919 r/min	10.50 A	0.850	84.60 %	9.81 N·m	8.70
Y	--	50 Hz	380 V	3.00 kW	2910 r/min	6.15 A	0.880	84.60 %	9.81 N·m	8.30
D	--	50 Hz	220 V	3.00 kW	2910 r/min	10.70 A	0.880	84.60 %	9.81 N·m	8.30
Y	--	60 Hz	440 V	3.00 kW	3520 r/min	5.53 A	0.890	84.50 %	8.13 N·m	9.80
Y	--	60 Hz	460 V	3.00 kW	3527 r/min	5.62 A	0.840	84.50 %	8.12 N·m	10.30

Gross Weight	37 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 84.6 % Partial Load (75%) 83.6 % Partial Load (50%) 81.2 %
IE Class Data (60 Hz)	IE Class IE1 Full Load (100%) 84.5 % Partial Load (75%) 82.8 % Partial Load (50%) 79.3 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2BAX 100LA 2
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	32 kg
Product Type	EBA2__M2BAX_CI
Quote Only	No
SCIP	d19446d4-4db6-4ddb-826d-2341a0f7dd46 Finland (FI)
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Menden, Germany Shanghai, China
Temperature Class Default	--
Temperature Rise	80 K
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Cast Iron Motors

