


PRODUCT-DETAILS

3GBA113410-BSD

M2BAX 112MLA 6



General Information

Product ID	3GBA113410-BSD
ABB Type Designation	M2BAX 112MLA 6
Catalog Description	M2BAX 112MLA 6

Additional Information

ABB Type Designation	M2BAX 112MLA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	China (CN)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	2.20 kW	951 r/min	5.31 A	0.710	84.30 %	22.00 N·m	5.80
D	--	50 Hz	230 V	2.20 kW	951 r/min	9.23 A	0.710	84.30 %	22.00 N·m	5.80
Y	--	50 Hz	380 V	2.20 kW	944 r/min	5.29 A	0.750	84.30 %	22.15 N·m	5.40
D	--	50 Hz	220 V	2.20 kW	944 r/min	9.13 A	0.750	84.30 %	22.15 N·m	5.40
Y	--	50 Hz	415 V	2.20 kW	954 r/min	5.34 A	0.680	84.30 %	21.91 N·m	6.00

Gross Weight

51 kg

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 84.3 % Partial Load (75%) 83.8 % Partial Load (50%) 81.6 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 87.5 % Partial Load (75%) 87.1 % Partial Load (50%) 85.6 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2BAX 112MLA 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	46 kg
Product Type	EBA3__M2BAX_CI
Quote Only	No
SCIP	d19446d4-4db6-4ddb-826d-2341a0f7dd46 Finland (FI)
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany Shanghai, China
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE3 Premium Efficiency Cast Iron Motors

