


PRODUCT-DETAILS

# 3GBA201420-ASCCN

## M2BAX 200MLB2



### General Information

|                      |                  |
|----------------------|------------------|
| Product ID           | 3GBA201420-ASCCN |
| ABB Type Designation | M2BAX 200MLB 2   |
| Catalog Description  | M2BAX 200MLB2    |

### Additional Information

|                       |                |
|-----------------------|----------------|
| ABB Type Designation  | M2BAX 200MLB 2 |
| Altitude              | 1000 m         |
| Ambient Temperature   | 40 °C          |
| Bearing               | 6212-2Z/C3     |
| Bearing NDE           | 6209-2Z/C3     |
| Country of Origin     | China (CN)     |
| Customs Tariff Number | 85015100       |
| Direction of Rotation | Both sides     |
| Electrical Data       |                |

| Conn | Temp Class | Freq  | Voltage | Power    | Speed      | Current  | Power Factor | Efficiency | Torque     | IS/IN |
|------|------------|-------|---------|----------|------------|----------|--------------|------------|------------|-------|
| Y    | --         | 50 Hz | 400 V   | 37.00 kW | 2951 r/min | 64.20 A  | 0.900        | 92.50 %    | 119.75 N·m | 7.90  |
| D    | --         | 50 Hz | 230 V   | 37.00 kW | 2951 r/min | 111.00 A | 0.900        | 92.50 %    | 119.75 N·m | 7.90  |
| Y    | --         | 50 Hz | 380 V   | 37.00 kW | 2944 r/min | 67.00 A  | 0.910        | 92.50 %    | 120.01 N·m | 7.20  |
| D    | --         | 50 Hz | 220 V   | 37.00 kW | 2944 r/min | 116.00 A | 0.910        | 92.50 %    | 120.01 N·m | 7.20  |
| Y    | --         | 60 Hz | 440 V   | 37.00 kW | 3552 r/min | 57.00 A  | 0.920        | 93.00 %    | 99.46 N·m  | 8.60  |
| Y    | --         | 60 Hz | 460 V   | 37.00 kW | 3557 r/min | 55.90 A  | 0.900        | 93.00 %    | 99.32 N·m  | 9.20  |

|                           |                                                                                                   |
|---------------------------|---------------------------------------------------------------------------------------------------|
| Gross Weight              | 239 kg                                                                                            |
| IC Class                  | IC411                                                                                             |
| IE Class Data (50 Hz)     | IE Class IE2<br>Full Load (100%) 92.5 %<br>Partial Load (75%) 92.7 %<br>Partial Load (50%) 92.3 % |
| IE Class Data (60 Hz)     | IE Class IE3<br>Full Load (100%) 93.0 %<br>Partial Load (75%) 92.6 %<br>Partial Load (50%) 91.6 % |
| IM Class                  | IMB3 IM1001                                                                                       |
| IP Class                  | IP55                                                                                              |
| Insulation Class          | ICLF                                                                                              |
| Invoice Description       | M2BAX 200MLB2                                                                                     |
| Lubrication               | For life                                                                                          |
| Made To Order             | No                                                                                                |
| Minimum Order Quantity    | 1 piece                                                                                           |
| Number of Poles (High)    | 2                                                                                                 |
| Order Multiple            | 1 piece                                                                                           |
| Package Level 1 Units     | 0 pallet (lift)                                                                                   |
| Product Name              | 3-Phase squirrel cage motor                                                                       |
| Product Net Weight        | 229 kg                                                                                            |
| Product Type              | CBA2__M2BAX_CI                                                                                    |
| Quote Only                | No                                                                                                |
| Selling Unit of Measure   | piece                                                                                             |
| Standards                 | IEC 60034-1                                                                                       |
| Starting of Motor         | Direct Online                                                                                     |
| Stocked At (Warehouses)   | Shanghai, China<br>Guangzhou, China                                                               |
| Temperature Class Default | --                                                                                                |
| Temperature Rise          | 80 K                                                                                              |
| Terminator Box Location   | D-End top                                                                                         |
| Two Speed Motor           | No                                                                                                |
| Type of Duty              | S1                                                                                                |
| UNSPSC                    | 26101100                                                                                          |
| Voltage Code              | S                                                                                                 |
| WEEE Category             | 4. Large Equipment (Any External Dimension More Than 50 cm)                                       |

---

## Categories

---

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Cast Iron Motors

