

PRODUCT-DETAILS

3GBA202410-BST

No Description Available



General Information

Product ID	3GBA202410-BST
ABB Type Designation	M2BAX 200MLA 4
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M2BAX 200MLA 4
Bearing	6212-2Z/C3
Bearing NDE	6209-2Z/C3
Country of Origin	China (CN)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	30.00 kW	1472 r/min	57.30 A	0.820	90.70 %	193.40 N·m	6.60
D	--	50 Hz	230 V	30.00 kW	1472 r/min	99.30 A	0.820	90.70 %	193.40 N·m	6.60
Y	--	50 Hz	380 V	30.00 kW	1469 r/min	59.50 A	0.840	90.70 %	193.83 N·m	6.40
D	--	50 Hz	220 V	30.00 kW	1469 r/min	103.00 A	0.840	90.70 %	193.83 N·m	6.40
Y	--	60 Hz	440 V	30.00 kW	1773 r/min	51.00 A	0.840	91.70 %	160.66 N·m	7.80
Y	--	60 Hz	460 V	30.00 kW	1775 r/min	49.50 A	0.820	91.70 %	160.45 N·m	8.20
Gross Weight										232 kg
IC Class										IC411
IE Class Data (50 Hz)										IE Class IE1 Full Load (100%) 90.7 % Partial Load (75%) 91.0 % Partial Load (50%) 91.1 %
IE Class Data (60 Hz)										IE Class IE1 Full Load (100%) 91.7 % Partial Load (75%) 91.5 % Partial Load (50%) 90.9 %
IM Class										IMB5 IM3001
IP Class										IP55
Insulation Class										ICLF
Made To Order										No
Minimum Order Quantity										1 piece
Number of Poles (High)										4
Order Multiple										1 piece
Package Level 1 Units										0 pallet (lift)
Product Name										3-Phase squirrel cage motor
Product Net Weight										222 kg
Product Type										EBA1__M2BAX_CI
Quote Only										No
Selling Unit of Measure										piece
Temperature Class Default										--
Terminator Box Location										D-End top
Two Speed Motor										No
UNSPSC										26101100
Voltage Code										S

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE1 Standard Efficiency Cast Iron Motors

