

PRODUCT-DETAILS

3GBA202410-HED

M2BAX 200MLA 4



General Information

Product ID	3GBA202410-HED
ABB Type Designation	M2BAX 200MLA 4
Catalog Description	M2BAX 200MLA 4

Additional Information

ABB Type Designation	M2BAX 200MLA 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6212-2Z/C3
Bearing NDE	6209-2Z/C3
Country of Origin	Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	50 Hz	500 V	30.00 kW	1483 r/min	44.00 A	0.840	93.60 %	193.20 N·m	7.50
D	--	60 Hz	575 V	30.00 kW	1786 r/min	38.60 A	0.830	94.10 %	160.40 N·m	8.50

Gross Weight	269 kg
IC Class	IC411

IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 93.6 % Partial Load (75%) 93.8 % Partial Load (50%) 93.4 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 94.1 % Partial Load (75%) 94.0 % Partial Load (50%) 93.0 %
IM Class	IMB35 IM2001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2BAX 200MLA 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Pre Modified Motor Product ID	3GBA202410-AED
Product Name	3-Phase squirrel cage motor
Product Net Weight	259 kg
Product Type	EBA3__M2BAX_CI
Quote Only	No
SCIP	d19446d4-4db6-4ddb-826d-2341a0f7dd46 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	E

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE3 Premium Efficiency Cast Iron Motors



