

PRODUCT-DETAILS

3GBA203410-ASC

M2BAX 200MLA 6



General Information

Product ID	3GBA203410-ASC
ABB Type Designation	M2BAX 200MLA 6
Catalog Description	M2BAX 200MLA 6

Additional Information

ABB Type Designation	M2BAX 200MLA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6212-2Z/C3
Bearing NDE	6209-2Z/C3
Country of Origin	China (CN) Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	18.50 kW	979 r/min	39.30 A	0.750	90.40 %	180.03 N·m	6.30
D	--	50 Hz	230 V	18.50 kW	979 r/min	68.10 A	0.750	90.40 %	180.03 N·m	6.30
Y	--	50 Hz	380 V	18.50 kW	976 r/min	39.90 A	0.780	90.40 %	180.52 N·m	5.80
D	--	50 Hz	220 V	18.50 kW	976 r/min	69.00 A	0.780	90.40 %	180.52 N·m	5.80
Y	--	60 Hz	440 V	18.50 kW	1180 r/min	34.80 A	0.760	91.70 %	149.40 N·m	6.70
Y	--	60 Hz	460 V	18.50 kW	1182 r/min	34.60 A	0.730	91.70 %	149.15 N·m	7.00

Gross Weight	215 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 90.4 % Partial Load (75%) 89.2 % Partial Load (50%) 89.5 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 91.7 % Partial Load (75%) 91.0 % Partial Load (50%) 89.7 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2BAX 200MLA 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	205 kg
Product Type	EBA2__M2BAX_CI
Quote Only	No
SCIP	d19446d4-4db6-4ddb-826d-2341a0f7dd46 Finland (FI)
Selling Unit of Measure	piece
Stocked At (Warehouses)	Shanghai, China
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Cast Iron Motors

