

PRODUCT-DETAILS

3GBA222210-ADD

M2BAX 225SMA 4



General Information

Product ID	3GBA222210-ADD
ABB Type Designation	M2BAX 225SMA 4
Catalog Description	M2BAX 225SMA 4

Additional Information

ABB Type Designation	M2BAX 225SMA 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6213-2Z/C3
Bearing NDE	6210-2Z/C3
Country of Origin	Poland (PL) China (CN)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	37.00 kW	1482 r/min	39.80 A	0.830	93.90 %	238.60 N-m	7.20
D	--	50 Hz	400 V	37.00 kW	1482 r/min	68.90 A	0.830	93.90 %	238.60 N-m	7.20
Y	--	50 Hz	660 V	37.00 kW	1477 r/min	40.80 A	0.850	93.90 %	239.10 N-m	6.50
D	--	50 Hz	380 V	37.00 kW	1477 r/min	71.20 A	0.850	93.90 %	239.10 N-m	6.50
D	--	60 Hz	440 V	37.00 kW	1781 r/min	61.60 A	0.840	94.50 %	198.30 N-m	8.10
D	--	60 Hz	460 V	37.00 kW	1783 r/min	59.30 A	0.830	94.50 %	198.12 N-m	8.80

Gross Weight	284 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 93.9 % Partial Load (75%) 94.1 % Partial Load (50%) 93.8 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 94.5 % Partial Load (75%) 94.7 % Partial Load (50%) 94.0 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2BAX 225SMA 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	274 kg
Product Type	EBA3__M2BAX_CI
Quote Only	No
SCIP	d19446d4-4db6-4ddb-826d-2341a0f7dd46 Finland (FI)
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE3 Premium Efficiency Cast Iron Motors

