

PRODUCT-DETAILS

3GBA222210-HSC

No Description Available



General Information

Product ID	3GBA222210-HSC
ABB Type Designation	M2BAX 225SMA 4
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M2BAX 225SMA 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6213-2Z/C3
Bearing NDE	6210-2Z/C3
Country of Origin	Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	37.00 kW	1479 r/min	71.10 A	0.800	92.70 %	238.90 N·m	7.60
D	--	50 Hz	230 V	37.00 kW	1479 r/min	124.00 A	0.800	92.70 %	238.90 N·m	7.60
Y	--	50 Hz	380 V	37.00 kW	1477 r/min	72.30 A	0.830	92.70 %	238.90 N·m	7.10
D	--	50 Hz	220 V	37.00 kW	1477 r/min	124.00 A	0.830	92.70 %	238.90 N·m	7.10
Y	--	60 Hz	440 V	37.00 kW	1779 r/min	62.80 A	0.830	93.00 %	198.48 N·m	8.40
Y	--	60 Hz	460 V	37.00 kW	1781 r/min	61.80 A	0.830	93.00 %	198.28 N·m	8.90

Gross Weight	275 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 92.7 % Partial Load (75%) 92.6 % Partial Load (50%) 92.2 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 93.0 % Partial Load (75%) 92.6 % Partial Load (50%) 91.8 %
IM Class	IMB35 IM2001
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Pre Modified Motor	3GBA222210-ASC
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	265 kg
Product Type	EBA2__M2BAX_CI
Quote Only	No
SCIP	d19446d4-4db6-4ddb-826d-2341a0f7dd46 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Cast Iron Motors

