

PRODUCT-DETAILS

3GBA222220-ADF

M2BAX 225SMB 4



General Information

Product ID	3GBA222220-ADF
ABB Type Designation	M2BAX 225SMB 4
Catalog Description	M2BAX 225SMB 4

Additional Information

ABB Type Designation	M2BAX 225SMB 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6213-2Z/C3
Bearing NDE	6210-2Z/C3
Country of Origin	China (CN) Poland (PL)
Customs Tariff Number	85015290
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	45.00 kW	1481 r/min	49.30 A	0.810	94.20 %	290.48 N·m	8.20
D	--	50 Hz	400 V	45.00 kW	1481 r/min	85.10 A	0.810	94.20 %	290.20 N·m	8.20
Y	--	50 Hz	660 V	45.00 kW	1481 r/min	49.70 A	0.840	94.20 %	290.48 N·m	8.20
D	--	50 Hz	380 V	45.00 kW	1481 r/min	86.40 A	0.840	94.20 %	290.48 N·m	8.20

Gross Weight	303 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 94.2 % Partial Load (75%) 94.3 % Partial Load (50%) 94.0 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 95.0 % Partial Load (75%) 94.7 % Partial Load (50%) 94.1 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2BAX 225SMB 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	293 kg
Product Type	EBA3__M2BAX_CI
Quote Only	No
Replaced Product ID (OLD)	3GBA222220-ADD
SCIP	d19446d4-4db6-4ddb-826d-2341a0f7dd46 Finland (FI)
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE3 Premium Efficiency Cast Iron Motors

