

PRODUCT-DETAILS

3GBA312220-ADM701

M2BAX 315SMB 4



General Information

Product ID	3GBA312220-ADM701
ABB Type Designation	M2BAX 315SMB 4
Catalog Description	M2BAX 315SMB 4

Additional Information

ABB Type Designation	M2BAX 315SMB 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6219/C3
Bearing NDE	6217/C3VL0241
Country of Origin	Poland (PL)
Customs Tariff Number	85015381
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	110.00 kW	1489 r/min	113.00 A	0.850	95.40 %	705.00 N·m	7.00
D	--	50 Hz	400 V	110.00 kW	1489 r/min	196.00 A	0.850	95.40 %	705.00 N·m	7.00
Y	--	50 Hz	660 V	110.00 kW	1488 r/min	116.00 A	0.860	95.40 %	705.00 N·m	6.30
D	--	50 Hz	380 V	110.00 kW	1488 r/min	201.00 A	0.860	95.40 %	705.00 N·m	6.30

Gross Weight	843 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 95.4 % Partial Load (75%) 95.4 % Partial Load (50%) 94.8 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 95.8 % Partial Load (75%) 95.4 % Partial Load (50%) 95.2 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2BAX 315SMB 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Pre Modified Motor	3GBA312220-ADM
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	823 kg
Product Type	EBA3_M2BAX_CI
Quote Only	No
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE3 Premium Efficiency Cast Iron Motors

