

PRODUCT-DETAILS

3GBA312420-BDM188

M2BAX 315MLB 4



General Information

Product ID	3GBA312420-BDM188
ABB Type Designation	M2BAX 315MLB 4
Catalog Description	M2BAX 315MLB 4

Additional Information

ABB Type Designation	M2BAX 315MLB 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6319/C3
Bearing NDE	6316/C3
Country of Origin	Poland (PL)
Customs Tariff Number	85015381
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	200.00 kW	1487 r/min	203.00 A	0.860	96.00 %	1284.00 N-m	6.80
D	--	50 Hz	400 V	200.00 kW	1487 r/min	351.00 A	0.860	96.00 %	1284.00 N-m	6.80
Y	--	50 Hz	660 V	200.00 kW	1485 r/min	210.00 A	0.870	96.00 %	1284.00 N-m	6.10
D	--	50 Hz	380 V	200.00 kW	1485 r/min	364.00 A	0.870	96.00 %	1284.00 N-m	6.10
D	--	60 Hz	440 V	200.00 kW	1788 r/min	314.00 A	0.870	96.20 %	1068.00 N-m	7.10
D	--	60 Hz	460 V	200.00 kW	1788 r/min	305.00 A	0.860	96.20 %	1068.00 N-m	7.80

Gross Weight	1111 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 96.0 % Partial Load (75%) 96.3 % Partial Load (50%) 96.2 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 96.2 % Partial Load (75%) 96.2 % Partial Load (50%) 95.6 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2BAX 315MLB 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Pre Modified Motor	3GBA312420-BDM
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	1091 kg
Product Type	EBA3__M2BAX_CI
Quote Only	No
Selling Unit of Measure	piece
Service Factor	1.00
Stocked At (Warehouses)	Menden, Germany
Temperature Class	--
Default	
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE3 Premium Efficiency Cast Iron Motors

