


PRODUCT-DETAILS

3GBP132323-AFB

M3BP 132SMC 4



General Information

Product ID	3GBP132323-AFB
ABB Type Designation	M3BP 132SMC 4
Catalog Description	M3BP 132SMC 4

Additional Information

ABB Type Designation	M3BP 132SMC 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	China (CN) Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed
Y	--	50 Hz	500 V	7.50 kW	1450 r/min

Gross Weight	78 kg
--------------	-------

IC Class	IC411
----------	-------

IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 89.3 % Partial Load (75%) 90.1 % Partial Load (50%) 90.0 %
-----------------------	---

IE Class Data (60 Hz)	IE Class IE2
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3BP 132SMC 4
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Package Level 1 Units	1 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	73 kg
Product Type	3BP2__M3BP_IE2_CI
Quote Only	No
SCIP	54c45c7b-7581-40ab-b615-c1dcb277d8a7 Finland (FI)
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	F
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Cast Iron Motors

