

PRODUCT-DETAILS

3GBP223210-HSG

M3BP 225SMA 6



General Information

Product ID	3GBP223210-HSG
ABB Type Designation	M3BP 225SMA 6
Catalog Description	M3BP 225SMA 6

Additional Information

ABB Type Designation	M3BP 225SMA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6313/C3
Bearing NDE	6212/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	30.00 kW	986 r/min	56.20 A	0.830	92.60 %	290.00 N·m	7.00
D	--	50 Hz	230 V	30.00 kW	986 r/min	99.50 A	0.830	92.60 %	290.00 N·m	7.00
Y	--	50 Hz	415 V	30.00 kW	988 r/min	55.50 A	0.810	92.60 %	290.00 N·m	7.40
Y	--	60 Hz	440 V	30.00 kW	1187 r/min	50.30 A	0.840	93.00 %	241.00 N·m	7.40
Y	--	60 Hz	460 V	30.00 kW	1189 r/min	49.20 A	0.820	93.20 %	240.00 N·m	8.00

Gross Weight	359 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 92.6 % Partial Load (75%) 93.2 % Partial Load (50%) 92.6 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 93.0 % Partial Load (75%) 93.5 % Partial Load (50%) 92.7 %
IM Class	IMB35 IM2001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3BP 225SMA 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Pre Modified Motor Product ID	3GBP223210-ASG
Product Name	3-Phase squirrel cage motor
Product Net Weight	349 kg
Product Type	3BP2__M3BP_IE2_CI
Quote Only	No
Replaced Product ID (OLD)	3GBP223031-HSG
SCIP	54c45c7b-7581-40ab-b615-c1dcb277d8a7 Finland (FI)
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Cast Iron Motors

