

PRODUCT-DETAILS

3GBP223505-ADG

No Description Available



General Information

Product ID	3GBP223505-ADG
ABB Type Designation	M3BP V 225 SMA
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3BP V 225 SMA
Altitude	1000 m
Ambient Temperature	90 °C
Bearing	6313/C4
Bearing NDE	6212/C4
Country of Origin	Sweden (SE)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	tE	IS/IN
D	--	50 Hz	400 V	30.00 kW	989 r/min	58.00 A	0.810	0.00 %	0.00 N·m	0	0.00
Y	--	50 Hz	690 V	30.00 kW	989 r/min	35.00 A	0.810	0.00 %	0.00 N·m	0	0.00
Y	--	50 Hz	660 V	30.00 kW	987 r/min	35.00 A	0.820	0.00 %	0.00 N·m	0	0.00
D	--	50 Hz	380 V	30.00 kW	987 r/min	60.00 A	0.820	0.00 %	0.00 N·m	0	0.00
D	--	50 Hz	415 V	30.00 kW	990 r/min	56.00 A	0.800	0.00 %	0.00 N·m	0	0.00
D	--	60 Hz	440 V	30.00 kW	1190 r/min	51.00 A	0.800	0.00 %	0.00 N·m	0	0.00

Gross Weight	402 kg
IC Class	IC418
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLH
Made To Order	No
Minimum Order Quantity	1 piece
Moment of Inertia	0.00000 kg/m³
Number of Poles (High)	6
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	392 kg
Product Type	3BVS M3BPV Cast iron motor
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Västerås, Sweden
Temperature Class Default	--
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Cast Iron Motors

