

PRODUCT-DETAILS

3GBP282230-ASG

HIGH OUTPUT



General Information

Product ID	3GBP282230-ASG
ABB Type Designation	M3BP 280SMC 4
Catalog Description	HIGH OUTPUT

Additional Information

ABB Type Designation	M3BP 280SMC 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6316/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	110.00 kW	1486 r/min	193.00 A	0.860	95.10 %	707.00 N·m	7.60
D	--	50 Hz	230 V	110.00 kW	1486 r/min	336.00 A	0.860	95.10 %	707.00 N·m	7.60
Y	--	50 Hz	415 V	110.00 kW	1487 r/min	188.00 A	0.850	95.10 %	707.00 N·m	8.10
Y	--	60 Hz	460 V	110.00 kW	1786 r/min	169.00 A	0.860	95.20 %	587.00 N·m	8.70

Gross Weight	745 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 95.1 % Partial Load (75%) 95.2 % Partial Load (50%) 94.5 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 95.2 % Partial Load (75%) 95.2 % Partial Load (50%) 94.3 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	HIGH OUTPUT
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Output Power	110 kW
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	725 kg
Product Type	3BP2__M3BP_IE2_CI
Quote Only	No
SCIP	54c45c7b-7581-40ab-b615-c1dcb277d8a7 Finland (FI)
Selling Unit of Measure	piece
Service Factor	1.00
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100 39120000
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Cast Iron Motors
Motors and Generators → IEC Low Voltage AC Motors → Smoke Extraction Motors



