

PRODUCT-DETAILS

# 3GBP282430-BEM

No Description Available



## General Information

|                      |                          |
|----------------------|--------------------------|
| Product ID           | 3GBP282430-BEM           |
| ABB Type Designation | M3BP 280MLC 4            |
| Catalog Description  | No Description Available |

## Additional Information

|                       |               |
|-----------------------|---------------|
| ABB Type Designation  | M3BP 280MLC 4 |
| Altitude              | 1000 m        |
| Ambient Temperature   | 40 °C         |
| Bearing               | 6316/C3       |
| Bearing NDE           | 6316/C3       |
| Country of Origin     | Finland (FI)  |
| Customs Tariff Number | 85015381      |
| Direction of Rotation | Both sides    |

### Electrical Data

| Conn | Temp Class | Freq  | Voltage | Power     | Speed      | Current  | Power Factor | Efficiency | Torque     | IS/IN |
|------|------------|-------|---------|-----------|------------|----------|--------------|------------|------------|-------|
| D    | --         | 50 Hz | 500 V   | 132.00 kW | 1488 r/min | 200.00 A | 0.790        | 96.40 %    | 847.10 N·m | 7.10  |

|                       |                                                                      |
|-----------------------|----------------------------------------------------------------------|
| Gross Weight          | 910 kg                                                               |
| IC Class              | IC411                                                                |
| IE Class Data (50 Hz) | IE Class IE4<br>Full Load (100%) 96.4 %<br>Partial Load (75%) 96.4 % |

|                         |                                                             |
|-------------------------|-------------------------------------------------------------|
|                         | Partial Load (50%) 95.8 %                                   |
| IM Class                | IMB5 IM3001                                                 |
| IP Class                | IP55                                                        |
| Insulation Class        | ICLF                                                        |
| Made To Order           | No                                                          |
| Minimum Order Quantity  | 1 piece                                                     |
| Number of Poles (High)  | 4                                                           |
| Order Multiple          | 1 piece                                                     |
| Package Level 1 Units   | 0 pallet (lift)                                             |
| Product Name            | 3-Phase squirrel cage motor                                 |
| Product Net Weight      | 890 kg                                                      |
| Product Type            | 3BP4__M3BP_IE4_CI                                           |
| Quote Only              | No                                                          |
| SCIP                    | 54c45c7b-7581-40ab-b615-c1dcb277d8a7 Finland (FI)           |
| Selling Unit of Measure | piece                                                       |
| Temperature Class       | --                                                          |
| Default                 |                                                             |
| Terminator Box Location | Top                                                         |
| Two Speed Motor         | No                                                          |
| Type of Duty            | S1                                                          |
| UNSPSC                  | 26101100                                                    |
| Voltage Code            | E                                                           |
| WEEE Category           | 4. Large Equipment (Any External Dimension More Than 50 cm) |

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE4 Super Premium Efficiency Cast Iron Motors

