

PRODUCT-DETAILS

3GBP283230-HDM

No Description Available



General Information

Product ID	3GBP283230-HDM
ABB Type Designation	M3BP 280SMC 6
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3BP 280SMC 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6316/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI) India (IN)
Customs Tariff Number	85015290

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	55.00 kW	990 r/min	57.50 A	0.850	95.10 %	506.00 N-m	6.80
D	--	50 Hz	400 V	55.00 kW	990 r/min	99.40 A	0.850	95.10 %	506.00 N-m	6.80
D	--	50 Hz	415 V	55.00 kW	991 r/min	96.60 A	0.840	95.10 %	529.00 N-m	7.30

Gross Weight	745 kg
--------------	--------

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE4 Full Load (100%) 95.1 % Partial Load (75%) 95.2 % Partial Load (50%) 94.7 %
IM Class	IMB35 IM2001
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Pre Modified Motor	3GBP283230-ADM
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	725 kg
Product Type	3BP4__M3BP_IE4_CI
Quote Only	No
SCIP	54c45c7b-7581-40ab-b615-c1dcb277d8a7 Finland (FI)
Selling Unit of Measure	piece
Temperature Class	--
Default	
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE4 Super Premium Efficiency Cast Iron Motors



