

PRODUCT-DETAILS

3GBP313410-BSG

M3BP 315MLA 6



General Information

Product ID	3GBP313410-BSG
ABB Type Designation	M3BP 315MLA 6
Catalog Description	M3BP 315MLA 6

Additional Information

ABB Type Designation	M3BP 315MLA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6319/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	132.00 kW	993 r/min	240.00 A	0.830	95.30 %	1269.00 N-m	8.20
D	--	50 Hz	230 V	132.00 kW	993 r/min	418.00 A	0.830	95.30 %	1269.00 N-m	8.20
Y	--	50 Hz	415 V	132.00 kW	993 r/min	234.00 A	0.790	95.30 %	1271.00 N-m	8.70

Gross Weight	1170 kg
--------------	---------

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 95.3 % Partial Load (75%) 95.3 % Partial Load (50%) 94.7 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3BP 315MLA 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Output Power	132 kW
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	1150 kg
Product Type	3BP2__M3BP_IE2_CI
Quote Only	No
SCIP	54c45c7b-7581-40ab-b615-c1dcb277d8a7 Finland (FI)
Selling Unit of Measure	piece
Service Factor	1.00
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100 39120000
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Cast Iron Motors
Motors and Generators → IEC Low Voltage AC Motors → Smoke Extraction Motors



