

PRODUCT-DETAILS

3GBP351410-BDK

M3BP 355MLA 2



General Information

Product ID	3GBP351410-BDK
ABB Type Designation	M3BP 355MLA 2
Catalog Description	M3BP 355MLA 2

Additional Information

ABB Type Designation	M3BP 355MLA 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6316M/C3
Bearing NDE	6316M/C3
Country of Origin	Finland (FI) China (CN) India (IN)
Customs Tariff Number	85015381
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	355.00 kW	2984 r/min	350.00 A	0.880	95.80 %	1136.00 N-m	7.20
D	--	50 Hz	400 V	355.00 kW	2984 r/min	603.00 A	0.880	95.80 %	1136.00 N-m	7.20
Y	--	50 Hz	660 V	355.00 kW	2981 r/min	361.00 A	0.890	95.80 %	1136.00 N-m	6.50
D	--	50 Hz	380 V	355.00 kW	2981 r/min	628.00 A	0.890	95.80 %	1137.00 N-m	6.50
D	--	50 Hz	415 V	355.00 kW	2985 r/min	588.00 A	0.870	95.80 %	1135.00 N-m	7.90
D	--	60 Hz	460 V	355.00 kW	3586 r/min	528.00 A	0.880	95.80 %	945.00 N-m	8.10

Gross Weight	2030 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 95.8 % Partial Load (75%) 95.5 % Partial Load (50%) 94.7 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 95.8 % Partial Load (75%) 95.3 % Partial Load (50%) 94.2 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3BP 355MLA 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	2000 kg
Product Type	3BP3_M3BP_IE3_CI
Quote Only	No
SCIP	54c45c7b-7581-40ab-b615-c1dcb277d8a7 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Cast Iron Motors

