

PRODUCT-DETAILS

3GBP352220-AXG

M3BP 355SMB 4



General Information

Product ID	3GBP352220-AXG
ABB Type Designation	M3BP 355SMB 4
Catalog Description	M3BP 355SMB 4

Additional Information

ABB Type Designation	M3BP 355SMB 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6322/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI) China (CN) Poland (PL)
Customs Tariff Number	85015381
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	60 Hz	760 V	300.00 kW	1789 r/min	275.00 A	0.860	96.20 %	1601.00 N·m	7.40
D	--	60 Hz	440 V	300.00 kW	1789 r/min	476.00 A	0.860	96.20 %	1601.00 N·m	7.40
Y	--	60 Hz	660 V	300.00 kW	1784 r/min	314.00 A	0.870	96.20 %	1604.97 N·m	6.00
D	--	60 Hz	380 V	300.00 kW	1784 r/min	544.00 A	0.870	96.20 %	1605.06 N·m	5.90

Gross Weight	1810 kg
IC Class	IC411
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 96.2 % Partial Load (75%) 96.3 % Partial Load (50%) 95.9 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3BP 355SMB 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	1780 kg
Product Type	3BP2_ M3BP_IE2_CI
Quote Only	No
SCIP	54c45c7b-7581-40ab-b615-c1dcb277d8a7 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	X
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Cast Iron Motors



