

PRODUCT-DETAILS

3GBP353210-BSG

M3BP 355SMA 6



General Information

Product ID	3GBP353210-BSG
ABB Type Designation	M3BP 355SMA 6
Catalog Description	M3BP 355SMA 6

Additional Information

ABB Type Designation	M3BP 355SMA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6322/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI) China (CN)
Customs Tariff Number	85015381
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	160.00 kW	993 r/min	291.00 A	0.830	95.40 %	1538.00 N·m	7.00
D	--	50 Hz	230 V	160.00 kW	993 r/min	507.00 A	0.830	95.40 %	1538.00 N·m	7.00
Y	--	50 Hz	415 V	160.00 kW	994 r/min	284.00 A	0.820	95.40 %	1537.00 N·m	7.50

Gross Weight	1550 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 95.4 % Partial Load (75%) 95.3 % Partial Load (50%) 94.6 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3BP 355SMA 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Output Power	160 kW
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	1520 kg
Product Type	3BP2__M3BP_IE2_CI
Quote Only	No
SCIP	54c45c7b-7581-40ab-b615-c1dcb277d8a7 Finland (FI)
Selling Unit of Measure	piece
Service Factor	1.00
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100 39120000
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Marine Motors → Marine Process Performance Motors
 Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Cast Iron Motors
 Motors and Generators → IEC Low Voltage AC Motors → Smoke Extraction Motors



