

PRODUCT-DETAILS

3GBP353230-ASG

M3BP 355SMC 6



General Information

Product ID	3GBP353230-ASG
ABB Type Designation	M3BP 355SMC 6
Catalog Description	M3BP 355SMC 6

Additional Information

ABB Type Designation	M3BP 355SMC 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6322/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	250.00 kW	993 r/min	460.00 A	0.820	95.70 %	2404.00 N·m	7.40
D	--	50 Hz	230 V	250.00 kW	993 r/min	800.00 A	0.820	95.70 %	2404.00 N·m	7.40
Y	--	50 Hz	415 V	250.00 kW	994 r/min	454.00 A	0.800	95.70 %	2401.00 N·m	8.00

Gross Weight	0 kg
--------------	------

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 95.7 % Partial Load (75%) 95.7 % Partial Load (50%) 95.0 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3BP 355SMC 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	1820 kg
Product Type	3BP2__M3BP_IE2_CI
Quote Only	No
SCIP	54c45c7b-7581-40ab-b615-c1dcb277d8a7 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Cast Iron Motors

