

PRODUCT-DETAILS

3GBP354420-ASG

No Description Available



General Information

Product ID	3GBP354420-ASG
ABB Type Designation	M3BP 355MLB 8
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3BP 355MLB 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6322/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	250.00 kW	743 r/min	472.00 A	0.800	94.50 %	3213.00 N·m	7.50
D	--	50 Hz	230 V	250.00 kW	743 r/min	812.00 A	0.800	94.50 %	3213.00 N·m	7.50
Y	--	50 Hz	415 V	250.00 kW	743 r/min	467.00 A	0.780	94.50 %	3213.00 N·m	8.00

Gross Weight	0 kg
--------------	------

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 94.5 % Partial Load (75%) 94.7 % Partial Load (50%) 94.0 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	2180 kg
Product Type	3BP2__M3BP_IE2_CI
Quote Only	No
SCIP	54c45c7b-7581-40ab-b615-c1dcb277d8a7 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Cast Iron Motors

