

PRODUCT-DETAILS

3GBP356210-AEG

M3BP 355SMA 12



General Information

Product ID	3GBP356210-AEG
ABB Type Designation	M3BP 355SMA 12
Catalog Description	M3BP 355SMA 12

Additional Information

ABB Type Designation	M3BP 355SMA 12
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6322/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI) China (CN) Poland (PL)
Customs Tariff Number	85015381
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	50 Hz	500 V	90.00 kW	495 r/min	154.00 A	0.720	93.50 %	1736.00 N·m	5.70

Gross Weight	1550 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class NA

	Full Load (100%) 93.5 % Partial Load (75%) 93.5 % Partial Load (50%) 92.5 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3BP 355SMA 12
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	12
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	1520 kg
Product Type	3BP2__M3BP_IE2_CI
Quote Only	No
SCIP	54c45c7b-7581-40ab-b615-c1dcb277d8a7 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	E
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Cast Iron Motors

