

PRODUCT-DETAILS

3GBP359428-BDG

M3BP 355MLB 2/4



General Information

Product ID	3GBP359428-BDG
ABB Type Designation	M3BP 355MLB 2/4
Catalog Description	M3BP 355MLB 2/4

Additional Information

ABB Type Designation	M3BP 355MLB 2/4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6316M/C3
Bearing NDE	6316M/C3
Country of Origin	Finland (FI) China (CN) Poland (PL)
Customs Tariff Number	85015381
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
YY	--	50 Hz	400 V	310.00 kW	2983 r/min	510.00 A	0.910	96.20 %	992.00 N·m	8.10
D	--	50 Hz	400 V	200.00 kW	1491 r/min	425.00 A	0.710	96.20 %	1281.00 N·m	7.50

Gross Weight	2110 kg
--------------	---------

IC Class	IC411
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3BP 355MLB 2/4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Number of Poles (Low)	4
Output Power	310 kW
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	2080 kg
Product Type	3BP2__M3BP_IE2_CI
Quote Only	No
SCIP	54c45c7b-7581-40ab-b615-c1dcb277d8a7 Finland (FI)
Selling Unit of Measure	piece
Temperature Class	--
Default	
Terminator Box Location	Top
Two Speed Motor	Yes
Type of Duty	S1
UNSPSC	26101100 39120000
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Marine Motors → Marine Process Performance Motors

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Cast Iron Motors

Motors and Generators → IEC Low Voltage AC Motors → Smoke Extraction Motors

