

PRODUCT-DETAILS

3GBP404810-ADG

M3BP 400LKA 8



General Information

Product ID	3GBP404810-ADG
ABB Type Designation	M3BP 400LKA 8
Catalog Description	M3BP 400LKA 8

Additional Information

ABB Type Designation	M3BP 400LKA 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6324/C3
Bearing NDE	6319/C3
Country of Origin	Finland (FI) China (CN)
Customs Tariff Number	85015381

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	315.00 kW	744 r/min	345.00 A	0.810	93.50 %	4043.00 N-m	7.00
D	--	50 Hz	400 V	315.00 kW	744 r/min	592.00 A	0.810	93.50 %	4043.00 N-m	7.00
D	--	50 Hz	415 V	315.00 kW	744 r/min	585.00 A	0.780	93.50 %	4040.00 N-m	6.80

Gross Weight	2940 kg
--------------	---------

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 93.5 % Partial Load (75%) 93.3 % Partial Load (50%) 92.7 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3BP 400LKA 8
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Output Power	315 kW
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	2900 kg
Product Type	3BP2__M3BP_IE2_CI
Quote Only	No
SCIP	54c45c7b-7581-40ab-b615-c1dcb277d8a7 Finland (FI)
Selling Unit of Measure	piece
Stocked At (Warehouses)	Shanghai, China
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100 39120000
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Marine Motors → Marine Process Performance Motors
Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Cast Iron Motors
Motors and Generators → IEC Low Voltage AC Motors → Smoke Extraction Motors



