

PRODUCT-DETAILS

3GGP071321-CSB

M3GP 71MA 2



General Information

Product ID	3GGP071321-CSB
ABB Type Designation	M3GP 71MA 2
Catalog Description	M3GP 71MA 2

Additional Information

ABB Type Designation	M3GP 71MA 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6203-2Z/C3
Bearing NDE	6202-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
EX-Protection	Exec

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	400 V	0.37 kW	2785 r/min	0.91 A	0.790	69.50 %	1.26 N·m	4.60
D	T3	50 Hz	230 V	0.37 kW	2785 r/min	1.57 A	0.790	69.50 %	1.26 N·m	4.60
Y	T3	60 Hz	460 V	0.37 kW	3425 r/min	0.80 A	0.750	72.00 %	1.03 N·m	5.80

Gas Group	IIC
Gross Weight	14 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 69.5 % Partial Load (75%) 70.8 % Partial Load (50%) 67.8 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 72.0 % Partial Load (75%) 71.4 % Partial Load (50%) 66.6 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 71MA 2
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor	3GGP071321-BSB
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	11 kg
Product Type	3GP0__M3GP_CI
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Temperature Class	T3
Default	
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors



