


PRODUCT-DETAILS

3GGP071350-CEL

M3GP 71ME 2



General Information

Product ID	3GGP071350-CEL
ABB Type Designation	M3GP 71ME 2
Catalog Description	M3GP 71ME 2

Additional Information

ABB Type Designation	M3GP 71ME 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6203-2Z/C3
Bearing NDE	6202-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
EX-Protection	Exec

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	T3	50 Hz	500 V	0.55 kW	2755 r/min	1.00 A	0.830	77.80 %	1.90 N·m	6.80

Gas Group	IIC
Gross Weight	14 kg
IC Class	IC411

IE Class Data (50 Hz)

IE Class IE3
Full Load (100%) 77.8 %
Partial Load (75%) 79.3 %
Partial Load (50%) 78.4 %

IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 71ME 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor	3GGP071350-BEL
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	11 kg
Product Type	5GP3 M3GP CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class	T3
Default	
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	E
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors

