

PRODUCT-DETAILS

3GGP072322-CEB

M3GP 71MB 4



General Information

Product ID	3GGP072322-CEB
ABB Type Designation	M3GP 71MB 4
Catalog Description	M3GP 71MB 4

Additional Information

ABB Type Designation	M3GP 71MB 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6203-2Z/C3
Bearing NDE	6202-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
EX-Protection	Exec

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	T3	50 Hz	500 V	0.37 kW	1411 r/min	0.77 A	0.740	72.70 %	2.50 N·m	5.20

Gas Group	IIC
Gross Weight	15 kg
IC Class	IC411

IE Class Data (50 Hz)		IE Class IE2
		Full Load (100%) 72.7 %
		Partial Load (75%) 73.3 %
		Partial Load (50%) 69.9 %
IM Class		IMB14 IM3601
IP Class		IP55
Insulation Class		ICLF
Invoice Description		M3GP 71MB 4
Lubrication		For life
Made To Order		No
Minimum Order Quantity		1 piece
Number of Poles (High)		4
Order Multiple		1 piece
Package Level 1 Units		0 carton
Pre Modified Motor		3GGP072322-BEB
Product ID		
Product Name		3-Phase squirrel cage motor
Product Net Weight		12 kg
Product Type		3GP0__M3GP_CI
Quote Only		No
Selling Unit of Measure		piece
Standards		IEC 60034-1
Starting of Motor		Direct Online
Temperature Class		T3
Default		
Terminator Box Location		Top
Two Speed Motor		No
Type of Duty		S1
UNSPSC		26101100
Voltage Code		E
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors



