

PRODUCT-DETAILS

3GGP084310-ASH

M3GP 80MA 8



General Information

Product ID	3GGP084310-ASH
ABB Type Designation	M3GP 80MA 8
Catalog Description	M3GP 80MA 8

Additional Information

ABB Type Designation	M3GP 80MA 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
EX-Protection	Exec

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	400 V	0.18 kW	720 r/min	1.15 A	0.420	57.70 %	2.40 N·m	3.30
D	T3	50 Hz	230 V	0.18 kW	720 r/min	1.97 A	0.420	57.70 %	2.40 N·m	3.30
Y	T3	50 Hz	415 V	0.18 kW	722 r/min	1.18 A	0.400	56.30 %	2.39 N·m	3.30

Gas Group	IIC
Gross Weight	32 kg

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 56.3 % Partial Load (75%) 50.6 % Partial Load (50%) 41.5 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 80MA 8
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	29 kg
Product Type	3GP2__M3GP_IE2_CI
Quote Only	No
Replaced Product ID (OLD)	3GGP084310-ASG
Selling Unit of Measure	piece
Service Factor	1.00
Temperature Class Default	T3
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors



