

PRODUCT-DETAILS

3GGP102420-CSL

M3GP 100MLB 4



General Information

Product ID	3GGP102420-CSL
ABB Type Designation	M3GP 100MLB 4
Catalog Description	M3GP 100MLB 4

Additional Information

ABB Type Designation	M3GP 100MLB 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exec

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	400 V	3.00 kW	1444 r/min	6.10 A	0.810	87.70 %	19.80 N-m	7.00
D	T3	50 Hz	230 V	3.00 kW	1444 r/min	10.60 A	0.810	87.70 %	19.80 N-m	7.00
Y	T3	50 Hz	415 V	3.00 kW	1448 r/min	6.00 A	0.790	87.70 %	19.80 N-m	7.40

Gas Group	IIC
Gross Weight	47 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 87.7 % Partial Load (75%) 88.4 % Partial Load (50%) 87.6 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 87.5 % Partial Load (75%) 88.1 % Partial Load (50%) 87.3 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 100MLB 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor	3GGP102420-BSL
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	42 kg
Product Type	5GP3 M3GP CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class	T3
Default	
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors



