

PRODUCT-DETAILS

3GGP102510-BDL

M3GP 100LA 4



General Information

Product ID	3GGP102510-BDL
ABB Type Designation	M3GP 100LA 4
Catalog Description	M3GP 100LA 4

Additional Information

ABB Type Designation	M3GP 100LA 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exec

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	690 V	2.20 kW	1448 r/min	2.60 A	0.810	86.70 %	14.00 N-m	7.50
D	T3	50 Hz	400 V	2.20 kW	1448 r/min	4.50 A	0.810	86.70 %	14.00 N-m	7.50
D	T3	50 Hz	415 V	2.20 kW	1451 r/min	4.30 A	0.820	86.70 %	14.00 N-m	8.00

Gas Group	IIC
Gross Weight	43 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 86.7 % Partial Load (75%) 87.0 % Partial Load (50%) 85.6 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 87.5 % Partial Load (75%) 87.1 % Partial Load (50%) 85.0 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 100LA 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	38 kg
Product Type	5GP3 M3GP CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T3
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors



