


PRODUCT-DETAILS

3GGP103510-CSH

M3GP 100LA 6



General Information

Product ID	3GGP103510-CSH
ABB Type Designation	M3GP 100LA 6
Catalog Description	M3GP 100LA 6

Additional Information

ABB Type Designation	M3GP 100LA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2Z/C3
Bearing NDE	6206-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exec

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	400 V	1.50 kW	951 r/min	3.67 A	0.720	81.60 %	15.10 N·m	5.40
D	T3	50 Hz	230 V	1.50 kW	951 r/min	6.40 A	0.720	81.60 %	15.10 N·m	5.30
Y	T3	50 Hz	415 V	1.50 kW	955 r/min	3.69 A	0.700	81.00 %	15.05 N·m	5.60

Gas Group	IIC
Gross Weight	65 kg

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 80.0 % Partial Load (75%) 77.0 % Partial Load (50%) 79.0 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 100LA 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor Product ID	3GGP103510-BSH
Product Name	3-Phase squirrel cage motor
Product Net Weight	60 kg
Product Type	3GP2__M3GP_IE2_CI
Quote Only	No
Replaced Product ID (OLD)	3GGP103510-CSG
Selling Unit of Measure	piece
Temperature Class Default	T3
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors

