

PRODUCT-DETAILS

3GGP103870-ADK

No Description Available



General Information

Product ID	3GGP103870-ADK
ABB Type Designation	M3GP 100LKG 6
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3GP 100LKG 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exec
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	690 V	1.10 kW	969 r/min	1.55 A	0.680	81.00 %	10.90 N-m	4.10
D	T3	50 Hz	400 V	1.10 kW	969 r/min	2.60 A	0.680	81.00 %	10.90 N-m	4.10
Y	T3	50 Hz	660 V	1.10 kW	965 r/min	1.58 A	0.700	81.00 %	10.90 N-m	3.80
D	T3	50 Hz	380 V	1.10 kW	965 r/min	2.70 A	0.700	81.00 %	10.90 N-m	3.80
D	T3	50 Hz	415 V	1.10 kW	971 r/min	2.60 A	0.660	81.00 %	10.90 N-m	4.30
D	T3	60 Hz	460 V	1.10 kW	1171 r/min	2.30 A	0.660	88.00 %	9.00 N-m	4.60

Gas Group	IIC
Gross Weight	52 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 81.0 % Partial Load (75%) 80.8 % Partial Load (50%) 78.1 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 88.0 % Partial Load (75%) 87.5 % Partial Load (50%) 85.8 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	47 kg
Product Type	3GP3__M3GP_IE3_CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class	T3
Default	
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors

