


PRODUCT-DETAILS

3GGP104443-HHB

M3GP 100LC 8



General Information

Product ID	3GGP104443-HHB
ABB Type Designation	M3GP 100LC 8
EAN	3GGP104443-HHB
Catalog Description	M3GP 100LC 8

Additional Information

ABB Type Designation	M3GP 100LC 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EAN	3GGP104443-HHB
EX-Protection	ExnA

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor
D	T3	50 Hz	415 V	1.10 kW	705 r/min	3.20 A	0.630

Gas Group	II
Gross Weight	36 kg
IC Class	IC411

IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 74.9 % Partial Load (75%) 73.8 % Partial Load (50%) 69.4 %
IM Class	IMB35 IM2001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 100LC 8
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Package Level 1 Units	0 carton
Pre Modified Motor	3GGP104443-AHB
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	35 kg
Product Type	3GP0__M3GP_CI
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class	T3
Default	
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	H
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors

