

PRODUCT-DETAILS

3GGP104520-ADH

M3GP 100LB 8



General Information

Product ID	3GGP104520-ADH
ABB Type Designation	M3GP 100LB 8
Catalog Description	M3GP 100LB 8

Additional Information

ABB Type Designation	M3GP 100LB 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2Z/C3
Bearing NDE	6206-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exec

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	690 V	1.10 kW	717 r/min	2.08 A	0.570	70.80 %	14.60 N·m	3.70
D	T3	50 Hz	400 V	1.10 kW	717 r/min	3.60 A	0.570	70.80 %	14.60 N·m	3.70
D	T3	50 Hz	415 V	1.10 kW	719 r/min	4.20 A	0.480	70.80 %	14.60 N·m	3.30

Gas Group	IIC
Gross Weight	65 kg

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE1 Full Load (100%) 70.4 % Partial Load (75%) 67.1 % Partial Load (50%) 59.5 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 100LB 8
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	60 kg
Product Type	3GP2__M3GP_IE2_CI
Quote Only	No
Replaced Product ID (OLD)	3GGP104520-ADG
Selling Unit of Measure	piece
Temperature Class	T3
Default	
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors



