


PRODUCT-DETAILS

# 3GGP104820-BSK

No Description Available



## General Information

|                      |                          |
|----------------------|--------------------------|
| Product ID           | 3GGP104820-BSK           |
| ABB Type Designation | M3BP 100LKB 8            |
| Catalog Description  | No Description Available |

## Additional Information

|                       |               |
|-----------------------|---------------|
| ABB Type Designation  | M3BP 100LKB 8 |
| Altitude              | 1000 m        |
| Ambient Temperature   | 40 °C         |
| Bearing               | 6206-2Z/C3    |
| Bearing NDE           | 6205-2Z/C3    |
| Country of Origin     | Finland (FI)  |
| Customs Tariff Number | 85015220      |
| Direction of Rotation | Both sides    |
| EX-Protection         | Exec          |
| Electrical Data       |               |

| Conn | Temp Class | Freq  | Voltage | Power   | Speed     | Current | Power Factor | Efficiency | Torque    | IS/IN |
|------|------------|-------|---------|---------|-----------|---------|--------------|------------|-----------|-------|
| Y    | T3         | 50 Hz | 400 V   | 1.10 kW | 703 r/min | 3.08 A  | 0.650        | 77.70 %    | 14.90 N-m | 4.40  |
| D    | T3         | 50 Hz | 230 V   | 1.10 kW | 703 r/min | 5.34 A  | 0.650        | 77.70 %    | 14.90 N-m | 4.40  |
| Y    | T3         | 50 Hz | 380 V   | 1.10 kW | 695 r/min | 3.10 A  | 0.690        | 77.70 %    | 15.10 N-m | 4.10  |
| D    | T3         | 50 Hz | 220 V   | 1.10 kW | 695 r/min | 5.37 A  | 0.690        | 77.70 %    | 15.10 N-m | 4.10  |
| Y    | T3         | 50 Hz | 415 V   | 1.10 kW | 708 r/min | 3.12 A  | 0.620        | 77.70 %    | 14.80 N-m | 4.60  |
| Y    | T3         | 60 Hz | 460 V   | 1.10 kW | 860 r/min | 2.78 A  | 0.610        | 78.50 %    | 12.20 N-m | 4.90  |

|                         |                                                                                                   |
|-------------------------|---------------------------------------------------------------------------------------------------|
| Gas Group               | IIC                                                                                               |
| Gross Weight            | 50 kg                                                                                             |
| IC Class                | IC411                                                                                             |
| IE Class Data (50 Hz)   | IE Class IE3<br>Full Load (100%) 77.7 %<br>Partial Load (75%) 77.4 %<br>Partial Load (50%) 73.9 % |
| IE Class Data (60 Hz)   | IE Class IE3<br>Full Load (100%) 78.5 %<br>Partial Load (75%) 77.4 %<br>Partial Load (50%) 73.0 % |
| IM Class                | IMB5 IM3001                                                                                       |
| IP Class                | IP55                                                                                              |
| Insulation Class        | ICLF                                                                                              |
| Made To Order           | No                                                                                                |
| Minimum Order Quantity  | 1 piece                                                                                           |
| Number of Poles (High)  | 8                                                                                                 |
| Order Multiple          | 1 piece                                                                                           |
| Package Level 1 Units   | 0 carton                                                                                          |
| Product Name            | 3-Phase squirrel cage motor                                                                       |
| Product Net Weight      | 45 kg                                                                                             |
| Product Type            | 3GP3__M3GP_IE3_CI                                                                                 |
| Quote Only              | No                                                                                                |
| Selling Unit of Measure | piece                                                                                             |
| Temperature Class       | T3                                                                                                |
| Default                 |                                                                                                   |
| Terminator Box Location | D-End top                                                                                         |
| Two Speed Motor         | No                                                                                                |
| Type of Duty            | S1                                                                                                |
| UNSPSC                  | 26101100                                                                                          |
| Voltage Code            | S                                                                                                 |
| WEEE Category           | 5. Small Equipment (No External Dimension More Than 50 cm)                                        |

## Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors

