

PRODUCT-DETAILS

3GGP131322-CSB

M3GP 132SMB 2



General Information

Product ID	3GGP131322-CSB
ABB Type Designation	M3GP 132SMB 2
Catalog Description	M3GP 132SMB 2

Additional Information

ABB Type Designation	M3GP 132SMB 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exec

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	400 V	5.50 kW	2865 r/min	10.00 A	0.860	87.70 %	18.30 N-m	7.00
D	T3	50 Hz	230 V	5.50 kW	2865 r/min	17.40 A	0.860	87.70 %	18.30 N-m	7.00
Y	T3	60 Hz	460 V	5.50 kW	3485 r/min	8.70 A	0.870	86.00 %	15.00 N-m	8.00

Gas Group	IIC
Gross Weight	73 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 87.7 % Partial Load (75%) 88.4 % Partial Load (50%) 87.7 %
IE Class Data (60 Hz)	IE Class IE1 Full Load (100%) 86.0 % Partial Load (75%) 85.3 % Partial Load (50%) 82.8 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 132SMB 2
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor	3GGP131322-BSB
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	68 kg
Product Type	3GP0__M3GP_CI
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Temperature Class	T3
Default	
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors



